

Our IP65 LED dustproof is composed of a UV stabilized polycarbonate body which gives excellent protection from long-term degradation from sunlight as well as an IK08/5J optic impact rating. This stout luminaire is fully serviceable and rated for zone 21 and 22 applications

2 Foot, 4 Foot and 5 Foot EX DUSTPROOFS available. See our full brochure for all specifications to take on temperatures of up to 65°C ambient.



SPEC SHEET

EX Dustproof

Raw Lumen: Effective Lumen:

Power Factor:

Raw Efficacy: Effective Efficacy:

L90 B10 @ 25°: L80 B10 @ 35°:

Fitting Size 101mm x 101mm x:

2920 lm 2540 lm	
18W 0.95	29W 0.95
161 lm/w 140 lm/w	
>54 000 Hrs	

100	1	
ロノリ		m
	71111	

m	
m	
/w	
VV	

>50 000 Hrs

5840 lm 5052 lm	
36W	45W

165 lm/w 168 lm/w 143 lm/w 140 lm/w

>54 000 Hrs >50 000 Hrs

1280mm

7300 lm 8200 lm

50W 0.95 0.95

6230 lm 7010 lm

169 lm/w 166 lm/w 144 lm/w 142 lm/w

>54 000 Hrs >50 000 Hrs

1540mm

KEY FEATURES

3 SIZE OPTIONS

- EX Dustproof 2 Foot
- EX Dustproof 4 Foot
- EX Dustproof 5 Foot

DIFFUSER

Impact rating IK08/5J

TEMPERATURE

 Ambient room temperature -25°C to +35°C.



kV Protection: Up to 4kV, 10kV on request







Impact Resistance:



Housing Diffuser: **Polycarbonate**



Construction & Fasteners: Aluminum & SS316




Optional: Bluetooth, Wifi, Dali & Bi Level. Casambi App featured above



*25°C is for Textbooks, Not Africa's Sun: All EW Lights are designed for the 30°C Reality. Minimum.

Dustproof Distribution



Designed and Manufactured by energywise

Better Liaht Through Research

sales@energywise.co.za | www.energywise.co.za T: +27 31 764 2345 / +27 87 941 0012 Physical address: Unit 5 Edstan Business Park, 2 Ibhubesi Road, Riverhorse Valley, Durban, South Africa, 4017 Postal address: PO Box 1166, Kloof, South Africa, 3640

5 year warranty: Please visit www.energywise.co.za







