Get the job done, Glare-Free.

Specifically Built for industrial environments that need dependable performance without excessive brightness. The Bay XF offers exceptional balanced light distribution for a softer, more uniform light output, reducing glare while maintaining excellent illumination.

1140 x 195mm Bay XF 304

Raw Lumen: Effective Lumen:

Wattage: Raw Efficacy: Effective Efficacy:

Max Ta: L&B: Hrs:

12.720 lm 11,442 lm

72W 180 lm/w 162 lm/w

30°C L80 B10 50 000 Hrs 24,600 lm 21,726 lm

147W 168 lm/w 148 lm/w

30°C L80 B10 50 000 Hrs

Other sizes, lenses, drivers and wattages available. Call or email for full brochure and prices.



kV Protection: Up to 4kV



5000K standard 3000K, 4000K, 6500K available CR>80 R9>13



IP Rating: Indoor



Impact Resistance: IK08/5J



Lenses



Optional: Bluetooth, Wifi, Dali & Bi Level


P2000 Mount







Shackle /

Distribution Options



30°





KEY FEATURES

MODULAR

• With extra Lumen Packages up to 21,726 lm.

LENSES

• 4 different optics for multiple lens combinations.

3 SIZE OPTIONS

- Bay XF 104 1140x90mm
- Bay XF 204 1140x140mm
- Bay XF 304 **1140x195mm**

OPTICS

Impact rating IK08/5J

MOUNTING OPTIONS

- P2000 mount
- Ceiling mount
- Suspended / Pendant



Optional:

Bluetooth, Wifi, Dali & Bi Level. Casambi App featured above.







*25°C is for Textbooks, Not Africa's Sun: All EW Lights are designed for the 35°C Reality.

Designed and Manufactured by



Better Light Through Research

sales@energywise.co.za | www.energywise.co.za | T: +27 31 764 2345 Physical address: Unit 5 Edstan Business Park, 2 Ibhubesi Road, Riverhorse Valley, Durban, South Africa, 4017 Postal address: PO Box 1166, Kloof, South Africa, 3640

5 year warranty: Please visit www.energywise.co.za

