

polycarbonate body which gives excellent protection from long-term degradation from sunlight as well as an IK08/5J optic impact rating. This stout luminaire is fully serviceable and rated for zone 21 and 22 applications

2 Foot, 4 Foot and 5 Foot EX DUSTPROOFS available. See our full brochure for all specifications to take on temperatures of up to 65°C ambient.



## **SPEC SHEET**

# **EX** Dustproof

Raw Lumen: Effective Lumen:

Power Factor:

Raw Efficacy: Effective Efficacy:

L90 B10 @ 25°: L80 B10 @ 35°:

Fitting Size 101mm x 101mm x:

2920 lm 2540 lm		
18W 0.95	29W 0.95	
161 lm/w 140 lm/w		
>54 000 Hrs		

620mm

>50 000 Hrs

1		
n		
٧		
V		

5840 lm 5052 lm		
36W 0.95	45W 0.95	
165 lm/w 143 lm/w	,	
>54 000 Hrs >50 000 Hrs		
1000		

1280mm

### 7300 lm 8200 lm 6230 lm 7010 lm

50W 0.95 0.95

169 lm/w 166 lm/w 144 lm/w 142 lm/w

>54 000 Hrs >50 000 Hrs

1540mm

### **KEY FEATURES**

### 3 SIZE OPTIONS

- EX Dustproof 2 Foot
- EX Dustproof 4 Foot
- EX Dustproof 5 Foot

#### **DIFFUSER**

Impact rating IK08/5J

#### **TEMPERATURE**

 Ambient room temperature -25°C to +35°C.









**Impact** Resistance:



Housing Diffuser: **Polycarbonate** 

Designed and Manufactured by




Construction & Fasteners: Aluminum & SS316





\*25°C is for Textbooks, Not Africa's Sun: All EW Lights are designed for the 30°C Reality. Minimum.

## **Dustproof Distribution**



year warranty: Pléase visit www.energywise.co.za



Better Liaht Through Research

sales@energywise.co.za | www.energywise.co.za T: +27 31 764 2345 / +27 87 941 0012 Physical address: Unit 5 Edstan Business Park, 2 Ibhubesi Road, Riverhorse Valley, Durban, South Africa, 4017 Postal address: PO Box 1166, Kloof, South Africa, 3640



