

ZONE
21/22

ZONE
1/2

EX Pod

EX

IP
68

A standout luminaire with IP68 level protection & impressive operating temperature range.



This IP68 fitting is designed for durability in harsh environments and available for Zone 1/2 as well as Zone 21/22.

Ex tb IIIC T85° Db IP68

Ex db I Mb Underground

Ex db IIA Gb Surface

SPEC SHEET

EX POD 106

Raw Lumen:
Effective Lumen:

8830 lm
6160 lm

10,300 lm
7100 lm

240V:
Power Factor:
Raw Efficacy:
Effective Efficacy:

50W
0.95
176 lm/w
108 lm/w

66W
0.95
157 lm/w
108 lm/w

Max Ta:
L&B:

35°C
L90 B10

35°C
L80 B10

Dimensions:

2260mm x 50mm

KEY FEATURES

MODULAR

- With extra Lumen Packages up to 14,200 lm by pairing multiple pods.

4 SIZE OPTIONS

- EX Pod 1420mm
- EX Pod 1700mm
- EX Pod 1980mm
- EX Pod 2260mm



5 year warranty:

Please visit

www.energywise.co.za

CASING

- Impact rating IK08/5J (ZONE 21/22)
- Impact rating IK08/10J (ZONE 1/2)

TEMPERATURE

- Ambient room temperature -25°C to +40°C.



4kv
kV Protection:



5000K standard
3000K, 4000K,
6500K available
CR>80 R9>13



IP68
Indoor /
Outdoor



IK08/5J
Front cover:
IK08/5J




Modular



Plug & Play

4 Distribution Options



Designed and
Manufactured by

energywise

Better Light
Through Research.

sales@energywise.co.za | www.energywise.co.za

T: +27 31 764 2345 / +27 87 941 0012

Physical address: Unit 5 Edstan Business Park, 2 Ibhumbesi Road, Riverhorse Valley, Durban, South Africa, 4017

Postal address: PO Box 1166, Kloof, South Africa, 3640



**MASC
CERTIFIED**



**MADE IN
SOUTH AFRICA**