

LEDrail 2000



Designed specifically for slick and guick attachment to P2000 trunking thanks to its patented magnetic mounting plates the ledrail 2000 offers clean lines, cost effective installation and the ability to install in both continuous runs or staggered distributions with ease.



SPEC SHEET

LEDrail 2000 104

Raw Lumen: Effective Lumen:

240V:

Raw Efficacy: Effective Efficacy:

Max Ta: L&B:

4240 lm 3116 lm

24W 177 lm/w 130 lm/w

35°C L90 B10 F10 70K Hrs 5840 lm 4300 lm

32W 183 lm/w 134 lm/w

35°C L90 B10 F10 70K Hrs 6888 lm 4984 lm

41W 167 lm/w

35°C L80 B10 F10 70K Hrs

1150 x 45mm Fitting Length:

See our full brochure for other sizes and specifications.



kV Protection: 4kV or 10kV on request



3000K, 4000K, 6500K available CR>80 R9>13



IP Rating: Indoor



Modular: Expandable system

90

75

60



Diffúser



Recyclable



KEY FEATURES

MODULAR

 With extra Lumen Packages up to 14,900 lm.

DIFFUSER

 For a harmonious band of soft light.

5 SIZE OPTIONS

- LEDrail 2000 104
- LEDrail 2000 106
- LEDrail 2000 108
- LEDrail 2000 110
- LEDrail 2000 206 (double)

MOUNTING **OPTIONS**

P2000 mount









*25°C is for Textbooks, Not Africa's Sun: All EW Lights are designed for the 30°C Reality. Minimum.

90 **Distribution** 75 60 45

45 30 Wide Frosted

Designed and Manufactured by

energyw

Better Light Through Research

sales@energywise.co.za | www.energywise.co.za T: +27 31 764 2345 / +27 87 941 0012 Physical address: Unit 5 Edstan Business Park, 2 Ibhubesi Road, Riverhorse Valley, Durban, South Africa, 4017 Postal address: PO Box 1166, Kloof, South Africa, 3640





