LEDrail 4100 SABS



The undisputed king of retail lighting.

Our flagship linear retail LED solution designed standard with 1kV surge protection upgradeable to 4kV on request. Featuring eight lens options including retail symmetrical designed specifically for retail isles as well as the ability to upgrade to multi-wire circuit configurations and an almost tool-free installation. The LEDrail 4100 is a pre-wired linkable system with plug & play connections.



SPEC SHEET

LEDrail 4100 102

Raw Lumen: Effective Lumen:

240V: Raw Efficacy: Effective Efficacy:

Max Ta: L&B:

2920 lm 2557 lm

17W 174 lm/w 152 lm/w

40°C L90 B10 40°C 70K Hrs 3512 lm 3001 lm

21W 172 lm/w 147 lm/w

> 40°C L80 B10 40°C 70K Hrs

4975 lm 3957 lm

30W 168 lm/w 134 lm/w

40°C L80 B10 40°C 70K Hrs

Dimensions:

571mm x 51mm x 55mm



kV Protection: 4kV or 10kV on request











P2000




Optional: Bluetooth, Wifi, Dali & Bi Level




Recyclable



PMMA



Retail Asymmetrical



KEY FEATURES

OPTICS

• 8 different acrylic optics for multiple lens combinations.

5 SIZE OPTIONS

- LEDrail 4100 102
- LEDrail 4100 104
- LEDrail 4100 106
- LEDrail 4100 108
- LEDrail 4100 110

MOUNTING **OPTIONS**

- P2000 Compatible
- **Pendant**
- Floating
- Recessed

Designed and

Manufactured by



Optional: Bluetooth, Wifi, Dali & Bi Level. Casambi App



featured above



energy

Better Light Through Research.

sales@energywise.co.za | www.energywise.co.za T: +27 31 764 2345 / +27 87 941 0012 Physical address: Unit 5 Edstan Business Park, 2 Ibhubesi Road, Riverhorse Valley, Durban, South Africa, 4017 Postal address: PO Box 1166, Kloof, South Africa, 3640

5 year warranty: year warranty available <u>sнвы</u> | SABS T&Cs apply. Please visit

Lights are designed for the 30°C Reality. Minimum.



